



PART LIST

Make sure the following parts are included in the box.

ITEM	DESCRIPTION	QUANTITY
1	Side glass	2 off
2	Front glass	1 off
3	Plaster kit (3 off left side, 3 off right side)	6 off
4	Main housing	1 off
5	Front glass bottom support	1 off
6	Front glass bottom retainer	1 off
7	Front glass bottom retainer fixings	2 off
8	Fuel bed	1 off
9	Side glass top retainer (internal)	2 off
10	Side glass top retainer (internal) fixings	4 off
11	Plaster kit fixings	16 off
12	In-fill side piece fixings	16 off
13	In-fill right side	1 off
14	In-fill left side	1 off



**STEP 1;
REMOVAL OF THE FRONT GLASS (ITEM 2)**

1. Remove the 2 off fixings (item 7) that secure the front glass bottom retainer (item 6) to the fuel bed (item 8).
2. Lift off the front glass retainer (item 7) and using the glass suckers supplied (not shown) carefully remove the front glass (item 2).

**STEP 3;
REMOVAL OF THE PLASTER KIT (ITEM 3)**

1. Remove the plaster kit fixings (item 11) using a phillips screw driver (not supplied)

Note: Ensure to keep fixings for future reference.

2. Remove the plaster kit (item 3) from both sides of the unit.

**STEP 2;
REMOVAL OF THE SIDE GLASS (ITEM 1)**

1. Remove the 2 off side glass top retainer brackets (item 9) by taking out the 4 off fixings (item 10). 2 off on each bracket.

NOTE: If one wishes to install a corner model of the Electric the steps need only be executed for the corner that is not supposed to stay glass.

2. Carefully tilt the side glass inwards at the top and lift it away from unit.

**STEP 4;
FITTING IN THE IN-FILL SIDES
(ITEM 13 AND ITEM 14)**

1. Remove the In-fill side fixings (item 12)
2. Place the in-fill sides over the existing side pieces
3. Using the in-fill side fixings (item 12) together with the plaster kit fixings (item 11) that were removed in the previous step secure the left and right in-fill sides (item 13 and 14) to the unit.